ESOF015-ECV Series

Outdoor Cabinet



There are lots of external forces can threaten the outdoor system, not only the temperature but also the humidity. Then the cooling function plays an important role in the power system, and the flexibility is also the common requirement to apply several kinds of electronics. ESOF015-ECV Series is developed for that.

Beside well protected by robust enclosure with IP55 class, the internal configuration can be adjusted easily, such as the numbers of wall layers, the type of thermal systems.

To keep the sensitive modules, batteries functioning in a high level and to reduce the CAPEX and OPEX, ESOF015-ECV Series is the ideal solution for the challenges. Your concern, our mission.

Key Features

- -48V_{DC} output for telecommunication applications
- Fan cooling
- IP55 protection class for outdoor application

Applications

- 3G / 4G / 5G
- Fixed Line
- Datacom



ESOF015-ECV Series



AC INPUT

| Voltage (nominal) | Single phase; 200 – 240V _{AC} ; 4W (L1, L2, N, PE) |
|-------------------------------|---|
| Voltage (range) | 200 – 240V _{AC} |
| Frequency | 50 / 60Hz |
| | |
| DC INPUT | |
| Voltage (nominal) | -54V _{DC} |
| Voltage (default) | -54V _{DC} |
| Voltage (adjustable range) | -43 to -58V _{DC} |
| Maximum Power @ nominal Input | Single phase: 8A (Max.) |
| MECHANICAL | |
| Dimensions (W x H x D) | 762 x 1829 x 1041mm (30 x 72 x 41in) |
| Weight | approx. 258kg (568.7lb) (battery excluded) |
| ENVIRONMENTAL | |
| Operating Temperature | -20 to +50 °C (-4 to +122 °F) |
| Storage Temperature | -40 to +70 °C (-40 to +158 °F) |
| Altitude | 0 to +3000m |
| Related Humidity | 95%, non-condensing (Max.) |
| Acoustic Noise | ≤ 65dBA |
| Cooling | Fan for power and equipment (6000W heat loss with $\Delta T \le 5 \text{ °C}$) |
| STANDARDS | |
| Environment | RoHS |

Delta Electronics Inc. 3 Tungyuan Road, Chungli Industrial Zone, Taoyuan City 32063, Taiwan. T +886 3 452 6107 / F +886 3 452 7314 www.deltaww.com

